

BEAM ANCHORS



| Product | Model # | Description |
|------------------------------|----------------|--|
| Fixed Beam Anchor | 2108406 | Works horizontally or vertically. Fits 1-1/2" (38mm) thick flange, 2-1/2 to 12" (63 to 304mm) wide, larger models available |
| Glyder2™ Sliding Beam Anchor | 2104700 | For complete horizontal mobility, designed for use with the Force2™ shock absorbing lanyard when used at the worker's feet. Easily installed and easily removed and taken to a new site. Integrated ratcheting adjustment system provides quick and easy installation and removal. NO MORE PINS AND CHAINS! Extremely lightweight at only 3.7 lbs. (1.66 kg), with a user capacity of 420 lbs. (189 kg). Fits flange 3-1/2" to 14" (9cm to 35 cm) wide, up to 1-1/4" (3cm) thick |
| Glyder™ Sliding Beam Anchor | 2110941 | For complete horizontal mobility, designed for use with the Force2™ shock absorbing lanyard when used at the worker's feet. Easily installed and easily removed and taken to a new site. Fits flange 6" to 18" (15cm to 45cm) wide, up to 2-1/2" (6.3cm) thick |
| Man Rated I-Beam Trolley | 2103143 | Designed for use on I-Beam Flanges ranging from 3" to 8" (7.6cm to 20.3cm) wide, up to 11/16" (17.5mm) thick. This anchorage connector rolls along an I-Beam providing horizontal mobility |

CONCRETE CONNECTORS



| Product | Description | Model # | Additional |
|------------------------------|---|----------------|---|
| Concrete D-Ring Anchor | Reusable D-Ring assembly—drill hole in set concrete, insert and torque anchor; for temporary or permanent applications; fits 11/16" (18mm) or 3/4" (19mm) holes (standard drill bits); connection swivels 360° | 2104560 | Standard model |
| | | 2104561 | D-ring assembly with 5 additional bolts |
| | | 2104562 | D-ring assembly with 11 additional bolts |
| | | 2100066 | Bolt kit, 10 pack |
| Leading Edge Concrete Anchor | Developed for work on pre-cast concrete; use with Leading Edge Ultra-Lok®; can also be used as end anchors for temporary horizontal lifeline; zinc plated steel | 2105500 | Use with 3504500 Ultra-Lok® Leading Edge Self-Retracting Lifeline |
| Concrete Anchor Strap | Provides temporary anchorage on concrete forms; loop slips over rebar, concrete is poured on top of loop and wear pad; once concrete sets, serves as 5,000 lb. (22kN) anchorage point; when no longer needed, simply cut strap and discard. Durable 1-3/4" (44mm) polyester webbing with full length outer wear pad; zinc plated steel D-ring | 2100050 | 3-1/2" (1m) length |
| | | 2100053 | 4' (1.2m) length |
| | | 2100061 | 3-1/2" (1m) length without D-ring, but with web loop |



| Product | Description | Model # | Additional |
|--------------------|---|----------------|--|
| Saflok® Carabiners | Self-closing/self-locking gate for increased safety and security, steel construction, user friendly even with gloves. Compatible with most connecting rings | 2000106 | 1-3/16" (30mm) gate opening |
| | | 2000113 | 1-3/16" (30mm) gate opening, 3,600 lb rated gate |
| | | 2000108 | 2-3/16" (55mm) gate opening |
| | | 2000114 | 2-3/16" (55mm) gate opening, 3,600 lb rated gate |
| | | 2000523 | 11/16" (17mm) gate opening |
| | | 2000112 | 11/16" (17mm) gate opening, 3,600 lb rated gate |
| | | 2000200 | 11/16" (17mm) gate opening, stainless steel |
| | | 2000300 | 2" (50mm) gate opening |
| | | 2000301 | 2" (50mm) gate opening, stainless steel |

NOTE: All part numbers are the same in Canada.